

Glue down (planks & tiles)

Version: 04/2024

Glue down	Contains	m ²	Gross Weight
1 pack planks ZENN	24 planks	5,20 m ²	18,96 kg
1 pallet planks ZENN (incl. pallet)	45 packs	234,11 m ²	873 kg
1 pack tiles ZENN	12 tiles	5,02 m ²	18,52 kg
1 pallet tiles ZENN (incl. pallet)	46 packs	230,77 m ²	872 kg

Product specifications	Norm	Glue down vinyl planks & tiles	
		Plank	Tile
Dimensions		L 1219,2 x W 177,8 mm	L 914,4 x W 457,2 mm
Total thickness	EN ISO 24346	2 mm	2 mm
Thickness of the wear layer	EN ISO 24340	0,3 mm	0,3 mm
Locking system		no	no
Usage classification	EN ISO 10874	23/31	23/31
Commercial warranty		3 years	3 years
Residential warranty		15 years	15 years

Test results

Underfloor heating		suitable max. 27° (80°F) / electrical floor heating systems: max 60 W/m ²
Castor chair	EN ISO 4918	pass
Fire resistance	EN 13501-1	Bfl-s1
Chemical resistance	EN ISO 26987	OK
Thermal resistance	ISO 8302	0,010 m ² K/W
Residual indentation	EN ISO 24343-1	≤ 0,1mm
Sound reduction: impact sound	EN ISO 10140-3	2 dB
Slip resistance	DIN 51130	R10
	EN ISO 13893	class DS
Dimensional stability	EN ISO 23999	< 0,15 % - pass
Light fastness	EN ISO 105 B02	≥ 6

